

## Round Safety Dampers



### True Round Fire Damper

- 1-1/2 Hour Fire Rated
- Spring Closure

### True Round Smoke Damper

- 350°F (177°C) Actuators
- UL Class I Leakage

### True Round Fire-Smoke Damper

- 1-1/2 Hour Fire Rated
- 350°F (177°C) Actuators
- EFL or PFL Controlled Closure



## Round Safety Dampers

Damper and Actuator  
Factory Assembled  
and Tested

# Round Safety Dampers

## Damper Configurators

Note: Not all configurations are available.

Ordering Code - FIRE		R	F	G	d	d	L	N	N	C
Product Family	R = Round Dampers	R								
Application	F = Fire		F							
Shroud Type	G = Galvanized 20-gauge			G						
Diameter	06 to 24 1 inch increments				0	6				
Actuation	L = 165°F actuation M = 212°F actuation H = 285°F actuation						L			
Control Signal	N = None							N		
Actuator	NC = Normally Closed								N	C

Ordering Code - SMOKE		R	S	G	d	d	N	D	N	C
Product Family	R = Round Dampers	R								
Application	S = Smoke		S							
Shroud Type	G = Galvanized 20-gauge			G						
Diameter	06 to 24 1 inch increments				0	6				
Actuation	N = None						N			
Control Signal	C = 120 VAC 350° F D = 24 VAC 350° F P = Pneumatic 350° F							D		
Actuator	NC = Normally Closed								N	C
Options	I = Indicator Switch Blade Position									

Ordering Code - FIRE/SMOKE		R	T	G	d	d	L	D	N	C	I
Product Family	R = Round Dampers	R									
Application	T = Fire/Smoke		T								
Shroud Type	G = Galvanized 20-gauge			G							
Diameter	06 to 24 1 inch increments				0	6					
Actuation	L = 165°F actuation M = 212°F actuation H = 250°F actuation						L				
Control Signal	C = 120 VAC 350° F D = 24 VAC 350° F P = Pneumatic 350° F							D			
Actuator	NC = Normally Closed								N	C	
Options	I = Indicator Switch Blade Position										I

### Our Guarantee to You

Certified to ISO 9001 quality processes and backed by a three-year warranty to the end user, our products have the **longest warranty in the business.**



All dampers are made to order and cannot be returned because of incorrectly ordered sizes.

### Shipping

Our round safety dampers are built-to-order with a **standard lead time of 15 working days.** Five-day fast track service is available for an additional charge.

