
# **CONTROL CABLES**



# **CONTROL CABLES**

The wire products listed on this data sheet are those most commonly used on HVAC installations. If you have requirements for materials not described on this page please contact BCCI for a complete list of products available, specifications and pricing.

PART NUMBER	GAUGE/ COND	WIRE	JACKET COLOR
PLENUM - UNSHIELDED			
W161P-2062	16/2C	Stranded	Wht, Grn
W181P-2051	18/2c	Stranded	Wht, Org, Blu, Brn,Grn, Pur, Pnk, Yell, Stripes
W183C-2052	18/3c	Stranded	Wht, Blu, Grn,Pur, Yell, Stripes
W184C-2099	18/4c	Stranded	Wht, Blu, Org, Stripes
W186C-2054	18/6c	Stranded	Wht, Blu, Org
W221P-2005	22/2c	Stranded	Wht,Org, Blu, Brn, Pur, Pnk, Yell
W224C-2057	22/4c	Stranded	Wht, Org, Pur
W226C-2083	22/6c	Stranded	Wht, Pur
W228C-2089	22/8c	Stranded	White
PLENUM - SHIELDED			
W161P-2084	16/2c	Stranded	Wht, Brn
W181P-2040	18/2c	Stranded	Wht, Org, Blu, Grn, Pur, Tan, Yell, Stripes
W183C-2058	18/3	Stranded	Wht, Ble, Grn, Org, Purp, Tan, Yell, Stripes
W184C-2059	18/4c	Stranded	Wht, Org, Blu, Yell
W186C-2055	18/6	Stranded	Wht, Org
W188C-2030	18/8c	Stranded	Wht, Blu
W221P-2044	22/2c	Stranded	Wht, Blu, Grn, Org, Purp, Yel, Stripes
W224C-2020	22/4c	Stranded	Wht, Org, Pur, Yel, Stripes
W226C-2077	22/6c	Stranded	Wht, Org, Stripes
PLENUM - SHIELDED LOW	CAP (12.5 Pf/	′Ft)	
W241P-2000F	24/2c	Stranded	Orange, Blue, Green
PLENUM - UNSHIELDED LO	ON CABLE		
W221P-2001	22/1Pr	Stranded	Blue, Orange, Purple, Yellow
NON-PLENUM - UNSHIELD	DED		
W181P-1002	18/2c	Stranded	Gray
W183C-1045	18/3c	Stranded	Gray
W184C-1037	18/4c	Stranded	Gray
W186C-1049	18/6c	Stranded	Gray
W224C-1057	22/4c	Stranded	Gray
W226C-1024	22/6c	Stranded	Gray
W228C-1906B	22/8c	Stranded	Gray
NON-PLENUM – SHIELDED	)		
W181P-1003	18/2c	Stranded	Gray
W183C-1240	18/3c	Stranded	Gray
W184C-1051	18/4c	Stranded	Gray
W221P-1001	18/6c	Stranded	Gray
W224C-1005	22/4c	Stranded	Gray
W226C-1042	22/6c	Stranded	Gray
W228C-1252	22/8c	Stranded	Gray

## **CONDUCTOR:**

 Stranded Bare or Tinned copper per ASTM B-3, B-8 and B-286

### **INSULATION:**

Premium grade color coded polymer Alloy

# SHIELD:

 Multi-Conductor: Overall polyester supported aluminum foil, plus a stranded tinned copper drain wire to facilitate grounding.

#### JACKET:

- Premium grade Natural polymer
- Suitable for use from 0 C to + 60 C
- Suggested voltage rating of 300 VRMS (multi-conductor cable only.)

#### **ALLOY:**

• Sequential footage markings to facilitate installation

### **INDUSTRY APPROVALS:**

 Plenum: Listed by UL as Type CMP and/or CL3P cables for use in NEC Article 800 and /or 725 installation

#### **PACKAGING:**

- 1000 ft. (305m) pay-out carton
- 1000 ft. (305m) spools or reels

# **OPTIONAL CONSTRUCTION:**

 Other jacket colors and PVC constructions may be available. Please consult your sales associate for futher information.

**Distributed By:** 



